

STOP & WASTE VALVE • HEAVY DUTY • 150 PSI**BRASS**

- Meets NSF approved low lead standards
- For use with water, oil or air
- Heavy construction
- Screw over bonnet
- Large flow area
- Large cast iron handle
- Allows draining of non-pressure side of valve when closed
- Threaded ends comply with ANSI B1.20.1
- Solder ends comply with ANSI B16.18

Part No.	UPC-A (032888)	Valve Size	Inner/Master Carton Qty.	Master Weight (lbs.)
Threaded				
105-183HC	050839	1/2"	12/NA	10
105-184HC	050846	3/4"	12/NA	12

Solder

105-683HC	055834	1/2"	12/NA	9
105-684HC	055841	3/4"	12/NA	10

STOP & WASTE • COMPRESSION • 125 PSI**BRASS**

- Meets NSF approved low lead standards
- CSA Certified – Canadian Standards Association
- For use with water, oil or air
- Compression ends for solderless connection to copper tubing
- Allows draining of non-pressure side of valve when closed

Part No.	UPC-A (032888)	Valve Size	Inner/Master Carton Qty.	Master Weight (lbs.)
105-613	056138	1/2" (5/8" O.D.)	12/72	46
105-614	056145	3/4" (7/8" O.D.)	6/36	32
105-613HC	056138	1/2" (5/8" O.D.)	16/NA	11
105-614HC	056145	3/4" (7/8" O.D.)	12/NA	11

BOILER DRAIN • 125 PSI**BRASS**

- Easy quarter turn operation
- Maximum 125 PSI working pressure
- Meets NSF approved low lead standards
- UPC approved, complies to ASME A112.18.1 standards
- Chrome plated brass ball
- P.T.F.E. seats
- Rust resistant handle
- 3/4" hose thread outlet
- Pipe threads comply with ANSI B1.20.1
- Hose threads comply with ANSI B1.20.7
- Solder ends comply with ANSI-16.18
- Patent no. D486204S valve body
- Patent no. D472962 valve handle

Part No.	UPC-A (032888)	Valve Size	Inner/Master Carton Qty.	Master Weight (lbs.)
Male Threaded				
102-053HC ♂	000414	1/2"	25/NA	8
102-054HC §	000421	3/4"	25/NA	9

♂ = 1/2" Male external threads and 1/2" internal solder connection
 § = 3/4" Male boiler drain is tapped 1/2" female thread